



Index

No.	Description	Remarks	Q'ty
1.	Main Body	Flame Retardant Resin	1
2.	Heat Sensor	Thermistor	1
3.	360° LED Indicator		1

Specifications

System Voltage	: 35 VDC
Operating Voltage Range	: 20 VDC to 38 VDC Peak
Standby Current	: 200 μ A
Alarm Current (with red LED)	: 6mA
Fixed Alarm Temperature	: 83 $^{\circ}$ C (181 $^{\circ}$ F)
360° LED Indicator	: Standby - Green LED Flash Alarm - Red LED Light
Applicable Standard	: UL521
UL Ambient Installation Temperature	: 0 $^{\circ}$ C (32 $^{\circ}$ F) to +65.6 $^{\circ}$ C (150 $^{\circ}$ F)
Operating Temperature	: -10 $^{\circ}$ C (14 $^{\circ}$ F) to +65.6 $^{\circ}$ C (150 $^{\circ}$ F)
Storage Temperature	: -40 $^{\circ}$ C (-40 $^{\circ}$ F) to +70 $^{\circ}$ C (158 $^{\circ}$ F)
Maximum Relative Humidity	: Up to 95%RH, non-condensing
Environment	: Indoor dry use only

NITAN COMPANY, LIMITED

SCALE	1 / 2	DATE	July 29, 2022
MODEL NO.	EVA-H3-H		
TITLE	Addressable Heat Detector (Fixed temperature)		
DRAWING NO.	N0100027	Dim:	mm